

# **PA30 Series Powered Air-Purifying Respirator**



Head Protection



Respiratory Protection



Fire and Rescue Safety



Thermal Imaging

# Comfortable, Effective, Reliable, Innovative

The PA30 Series protects workers against gases, vapors, and/or particulates when used according to Bullard's instructions. It accomplishes this, in part, by drawing ambient air through a filter/cartridge, and supplying that air through a breathing tube into the workers' headpiece.

Customer driven product development, as well as the incorporation of the latest technologies, culminate in the unique design and features of the PA30 Series.





## "Decon-Friendly" Housing

A smooth finish, sealed and gasketed design, and downward sloping configuration for easy "run-off" ensure that the blower will withstand the most rigorous of decon procedures. An optional decon belt completes the package.

#### **Battery Design**

Other PAPR external battery designs result in uneven weight distribution while also creating an additional "snag" hazard and decon concern. The battery packs on the PA30 are engineered inside the profile of the housing, with care taken to allow for easy removal and change-out. Two separate battery packs allow the user to carry only the amount of battery needed to get the job done. For 4-5 hours of performance, use one battery... for 8-10 hours install a second battery in the second port. The batteries are gasketed and the battery compartment is independent of the airflow chamber in order to maintain blower integrity.



#### **Battery Performance and Durability**

Unlike other conventional PAPRs that use outdated NiCad technology, the Bullard PA30 Series uses rechargeable Nickel Metal Hydride (NiMH) batteries that do not suffer the "memory" problems of NiCad. NiMH batteries contribute to the lightweight design of the PA30, while providing the worker up to 10 hours of battery performance on two battery packs.

### **Charger Technology**

Due to the combined characteristics of the NiMH batteries and the unique design of the Bullard chargers, the NiMH batteries will be kept at peak performance even if left on charge for long periods of time. The Bullard PA3SMC and PA3GC chargers offer a trickle charge feature, as well as voltage and temperature monitoring, which help assure that the batteries will be ready next week, next month, even next year!



#### **Audible Alarm**

In addition to the standard safeguards of a rotometerstyle airflow indicator which is used to check airflow prior to donning, Bullard has incorporated a 77dBA audible alarm to indicate low voltage. With this patented design, the alarm is positioned inside the breathing tube connector on the housing of the blower, so the sound is directed up the breathing tube and into the hood alerting the worker that he/she needs to exit the decontamination area and replace or recharge the battery.



## **PA30 Series Powered Air-Purifying Respirator**

#### **Sealed Power Switch**

The power switch is conveniently located for the worker to reach, and should not be accidentally switched off or on. The sealed design provides yet another assurance to workers that they are receiving the best protection a PAPR can offer.



## **Headtop Options**

The Bullard PA30 Series of PAPRs are approved for use with a wide range of headtops including the Bullard industry leading high performance Tychem® hoods and Tychem loose fitting facepieces. The Spectrum full facepiece is available in a PAPR configuration as a PA40 Series PAPR. All headtops are also available in supplied air configurations, allowing you to use one headpiece for both supplied air or powered air. See the selection guide for the full range of headpieces and other options.



## **Technical Specifications**

Dimensions41/2" W x 7" L x 51/2" H
Weight (blower & batteries)       2.65 lbs.         One battery       2.65 lbs.         Two batteries       3.35 lbs.         Decon belt       add .55 lbs.         Air Flow       >8 cfm
Battery Service Life One battery
Noise Level<66 dBA
Low Battery Alarm Noise Level<77 dBA
BatteriesNiMH
Warranty1 year











# **Ordering Information**

CATALOG NUMBER	DESCRIPTION	CATALOG NUMBER	DESCRIPTION
PA30 Systems		PA1BTS	Breathing Tube / Filter Seal
•		PA1SB	Standard Belt with Comfort Pad
PA30TJ3	PA3 Blower Assembly, 20TJ Hoods, PA1BT Breathing Tube, and PA3SMC Quick Charger	PA1DB	Decon Belt with Comfort Pad
DAGOTDG	<u> </u>	PA1EB	Extension Belt
PA30TP3 PA30TIC3	PA3 Blower Assembly, 20TP Hoods, PA1BT Breathing Tube, and	PA1DEB	Extension Belt - Decon
	PA3SMC Quick Charger	PA3PG	Plug for Blower Port (for use with PA3HE filters)
PASUTICS	PA3 Blower Assembly, 20TIC Hoods, PA1BT Breathing Tube, and	PA3BPC	Battery Port Covers
PA30TIC3DB PA30TPC3	PA3SMC Quick Charger PA3DB Blower Assembly with Decon Belt, 20TIC Hoods, PA1BT	PA3BP	Battery Pack (4 Hour capacity)
	Breathing Tube, and PA3SMC Quick Charger	PAPRBAG	Vinyl Storage Bag
	PA3 Blower Assembly, 20TPC Hoods, PA1BT Breathing Tube, and	Tychem Ho	ood Replacements
TASOTICS	PA3SMC Quick Charger	<b>2</b> 0TJ	Tychem QC Hood
PA30SIC3	PA3 Blower Assembly, 20SIC Hoods, PA1BT Breathing Tube, and	2013 20TJN	Tychem QC Hood - No Suspension
17303103	PA3SMC Quick Charger	2013IN 20TP	Tychem QC Hood with Solvent Resistant Lens
PA30SIC3DB	PA3DB Blower Assembly with Decon Belt, 20SIC Hoods, PA1BT	20TPN	Tychem QC Hood with Solvent Resistant Lens - No Suspension
	Breathing Tube, and PA3SMC Quick Charger	20TIC	Tychem QC Hood With Inner Bib
PA30LF3	PA3 Blower Assembly, 20LFL Loose Fitting Facepiece, PA20LFBT	20TICN	Tychem QC Hood With Inner Bib - No Suspension
	Breathing Tube, and PA3SMC Quick Charger	20TPC	Tychem QC Hood with Solvent Resistant Lens and Inner Bib
DARA Eller	5	20TPCN	Tychem QC Hood with Solvent Resistant Lens and Inner Bib - No
	/ Cartridge Replacements (6/pkg.)	ZOTI CIV	Suspension
PA3HE	High Efficiency Particulate Filters (HE)	20TICH	Tychem QC Hood for use with Bullard Hard Hat
PA30VAGHE	Organic Vapor/Acid Gas/High Efficiency Particulate Filter	20TICS	Tychem QC Hood with Taped and Sealed Seams
	Cartridges (OV/CL/CD/SD/HC/HF/HE)	20TICSN	Tychem QC Hood with Taped and Sealed Seams - No Suspension
PA3NBC	Acid Gas/Ammonia/Methylamine/Formaldehyde/High Efficiency	2011C3N 20SIC	Tychem SL Hood with Taped and Sealed Seams
	Particulate Filter Cartridges (CL/CD/SD/HC/HF/AM/MA/FM/HE)	20SICH	Tychem SL Hood with Taped and Sealed Seams for use with
PA30 Blowe	er Assemblies	2031011	Bullard Hard Hat
PA3	PA3BU Blower Unit (ivory, smooth finish) with Internal Voltage	20SICN	Tychem SL Hood with Taped and Sealed Seams - No Suspension
	alarm and standard PA1SB belt. Includes airflow indicator, PA3BP	Tychem Loose Fitting Facepiece Replacements	
	Battery Pack and PA3BPC Battery Port Cover. Breathing Tube and	20LFM	Loose Fitting Facepiece, Medium
	Charger sold separately	20LFM 20LFL	<b>9</b> , ·
PA3DB	PA3BU Blower Unit (ivory, smooth finish) with Internal Voltage		Loose Fitting Facepiece, Large
	alarm and vinyl decon PA1DB belt. Includes airflow indicator,	Mylar Lens	s covers
	PA3BP Battery Pack and PA3BPC Battery Port Cover. Breathing	20LCL	Adhesive-Edged Mylar Lens Covers
	Tube and Charger sold separately	Headband Suspensions for Tychem Hoods	
PA5	PA5BU Blower Unit (black, smooth finish) with Internal Voltage	20TG	Adjustable Headband Suspension
	alarm and standard PA1SB belt. Includes airflow indicator, PA3BP	20RT	Adjustable Ratchet Headband Suspension
	Battery Pack and PA3BPC Battery Port Cover. Breathing Tube and	20NC	Elastic Chin Strap
	Charger sold separately	Head Proto	ection for Model 20TICH and 20SICH
PA30 Repla	cement Parts		
PA3SMC	Quick Charger for PA3BP (2 ports)	3000WHT	Classic Hardhat (White)
PA3GC	Table-top Gang Charger (Quick - 5 ports)	3000RWHT	Classic Hardhat with 6-point Ratchet Suspension (White)
PA1BT	Hood Breathing Tube Assembly with clamp (Standard Length –	ESRTSL	6-Point Suspension for Model 3000 Classic Hardhat
	26")	ESULTRA	6-Point Ratchet Suspension for Model 3000 Classic Hardhat
PA1BTXS	Hood Breathing Tube Assembly with clamp (Short Length – 22")	5100WHT	Economy Hardhat (White)
PA20LFBT	Loose Fitting Facepiece Breathing Tube Assembly (Standard Length –	5100RWHT	Economy Hardhat with Ratchet Suspension (White)
	33")	TG600	4-Point Suspension for Model 5100 Economy Hardhat
PA20LFBTXS	Loose Fitting Facepiece Breathing Tube Assembly (Short Length –	TGRT600 ES42	4-Point Ratchet Suspension for Model 5100 Economy Hardhat
	26")	L342	Chin Strap



26")

S18051

Breathing Tube Clamp for PA1BT and PA1BTXS